



The D1200-2 series aluminum extension ladders have a duty rating of 225 lbs and interlocking side rails. The TRACTION-TRED® D rungs are slip resistant. Spring-loaded locks operate smoothly for easy operation. Shoes rest flat or are held in spur position with SHU-LOK® feature. Mar-resistant end caps help protect the surface ladder is leaning against. Exclusive ALFLO® rung joint means TWIST-PROOF® performance every time.


## Features

- Alflo rung joint for Twist-Proof performance
- Interlocking side rails
- Mar-resistant molded end caps
- Modified I-beam rails
- Rope and pulley system
- Rope clamp ties rope to rung
- Slip-resistant shoe with Shu-lok feature and spur plate
- Slip-resistant Traction-Tred D-rungs
- Spring loaded locks

## Dimensions

Feature	Size
Rails Dimension	3 in
Flange Dimension	1 in
Rung Dimension	1-3/4 in
Fly Width	15-1/4 in

# Specifications

Feature	Size / Details
Size	24 ft
Reach Height	23 ft
Max Working Length	21 ft
Extended Length	21 ft
Approx. Closed Length	12 ft
Style	Multi Section
Load Capacity	225 lbs
Type	Type II Duty Rating
Performance Rating	
Material	Aluminum
Rung Type	D-Rung
Foot Material	Slip-resistant pad
Number of Sections	2
Base Width	17-3/8 in outside rails
Certifications	ANSI A14.2 (2007); OSHA
Approx. Cu. Ft. Per Unit	8.6
Approx. Shipping Wt. Lbs.	33.5